

PYC275B

Prime Power: 200KW/250KVA

Standby Power: 220KW/275KVA

Voltage: 400V

Powered by Yuchai YC6MK350L-D20 Engine

Genset Performance

- 230/400V, 50Hz, 0.8PF, 3 Phases 4 wires
- Frequency drop $\leq 3\%$
- Voltage regulation $\leq 0.3\%$
- The steady state frequency $\leq 0.5\%$
- The steady state voltage deviation $\leq \pm 1\%$
- The transient frequency deviation $\leq +10\% \leq -15\%$
- The transient voltage deviation $\leq +20\% \leq -15\%$
- Frequency recovery time $\leq 3S$
- Voltage recovery time $\leq 1S(\text{Voltage} \pm 3\%)$
- THF (Telephone Harmonic Factor) < 3
- TIF (Telephone Influence Factor) < 50
Comply to Standard NEMA MG1-22.43
- Standard equipped with ambient temperature 40°C
Connecting radiator
- Built-in vibration isolator with high performance on
shock absorption.
- Product standards: (1) GB/T 2820-2022 / ISO8528:2018
(2) GB/T 4712-2008 (3) YD/T 502-2020 (4) YD/T 1051-2018

Optional Items

- Starting batteries
- Fuel tank
- Oil-water separator
- Sensor for low coolant level, low fuel/oil level
- Automatically monitoring & controlling system of city power
- Coolant heater
- Oil heater
- Heat exchanger--Water cooled tower system
- Silent type/Trailer
- Standardized container
- Design and construction of environmental protection; engineering for the Genset


Standard Configuration

- Guangxi Yu chai Engine
- Brushless synchronous alternator
- POWERTEC intelligent controller
- 40°C standard ambient temperature
(50°C Optional)
- Circuit breaker (3P)
- Float battery charger
- Battery connect wire
- Steel base frame
- Silencer, bellows, exhaust bend
- Bottom fuel tank
- Manual book and files



Diesel Engine

- Model: YC6MK350L-D20
- Yuchai YC6MK series engine adopts the world's advanced design concept and means. Adopt a number of modern diesel engine research and technical achievements to develop and design. Strong power, reliable quality, high efficiency and fuel saving, and the indicators have reached the international advanced level ;
- Structure: high-strength cylinder block, alloy forged steel crankshaft, alloy steel connecting rod and internal cooling oil gallery. The plug makes the engine more durable and lighter and more compact than other products .
- Adopting advanced four-valve and high-efficiency supercharging and intercooling technology, the air intake is sufficient and the combustion is sufficient. Low fuel consumption;
- Integral crankcase and integral cylinder head have good reliability; Wet cylinder liner is wear-resistant and easy to maintain..
- The piston adopts internal cooling oil passage technology, and the engine oil flowing through the piston takes away the heat of the piston in time. The piston can bear higher combustion temperature with high reliability.
- G3 performance requirements for generator set are met.



Alternator

- Optional brands: **Stamford / Marathon / Faraday / Engga / Mecc Alt**
- Brushless, 4 pole rotating magnetic field, single bearing with protective cover.
- Insulation: H Class.
- IP Class: IP23
- Cooling system
- AC exciter, rotate rectifying
- The stator winding is impregnated and the surface is covered with moisture-proof epoxy insulating paint.
- Rotor and exciter made with high temperature insulating resin, to satisfy tough environment.
- Rotor dynamic balancing complys for BS5625, class 2.5
- Sealed with advanced lubricating grease to prolong life of bearing.



Standard Meters

- 3 phases voltage: U_a, U_b, U_c
- Frequency F1
- Apparent power PR
- Power factor PF
- Coolant temperature WT
- Temperature $^{\circ}\text{C}$ display
- Oil pressure OP
- Engine speed
- 3 phases current: I_a, I_b, I_c
- Active power PA
- Power factor PF
- Temperature $^{\circ}\text{C}$ display
- KPa/Psi/Bar display
- Battery voltage V
- Running Hour
- Starting timer:(999999)



Standard Protection Function

Genset Protection

- Programmable I/O signal
- Emergency stop

Engine Protection

- Stop for over speed
- Low oil pressure
- High Coolant temperature
- Sensor fail
- Alarm for low/high battery voltage
- Low battery voltage
- Fail to start/Cranking fail

Alternator Protection

- Over Voltage
- Over current
- Voltage signal lost
- Over Voltage
- Over frequency
- Under frequency

Control System Components


- Manual/auto/stop/start
- Setting button
- Fault status indicators
- Screen menu selection button
- Emergency stop button
- Digital displayer



Communication Interface (Option)

- International standard MODBUS communication protocol RS232/ RS485 is suitable for remote control and monitor; It is easy integrated with SCADA;.

Genset	
Model	PYC275B
Prime Rating (kw)	200
Standby Rating (kw)	220
Rate current(A)	361
Power factor	0.8
Frequency(Hz)	50
Engine	
Engine Model	YC6MK350L-D20
Gross Engine output-Prime (kw)	235
Gross Engine output-Standby (kw)	258.9
Bore * stroke (mm)	123*145
Cylinders and structure	6 In line
Displacement(Liter)	10.34
Compression Ratio	16.8:1
Intake way	Turbocharged & Intercooled
Max intake resistance (KPa)	5
Air intake (m3/h)	918
Max exhaust back pressure (KPa)	10
Exhaust gas flow (m3/h)	2280
Exhaust temp (°C)	550
Cooling way	Water Radiator & Fan
Fan exhaust flow (m3/min)	612
Coolant capacity (L)	65
Highest water temperature(°C)	99
Minimum air opening to room (m2)	1.8/1.5
Thermostat range (°C)	80-90
Max oil temperature (°C)	120
Lubrication system oil capacity (L)	30
Rate load fuel consumption(L/H)	54.6
Standard Governor/Class	electronic
Emission	China Tier 2
Alternator	
Rated Voltage(V)	230/400
Output Way	3 Phases, 4 wires
Rated power factor	0.8
Exciter	Brushless, Self-exciter
Max voltage regulation	±1%
Phase	3
Protection class	IP21-23
Insulation class	H
Controller	
Brand	POWERTEC



Type	Dimension (mm) (L*W*H)	Weight (kg)	Fuel Tank Capacity (L)
Open Type	2900*1197*1599	2185	—
Silent Type	3500*1245*2052	3445	550

Contact Us

Powertec Generator System Inc.

Add: Danshui Yanna Industry Zone, Huiyang, Huizhou, Guangdong, China
Tel: +86 752-3911119 / 3911118
Fax: +86 752-3911110
Web: www.powertec.com.cn
Email: powertec@powertec.com.cn